### VILLAGE OF BARNWELL

### BY-LAW NO. 3-97 CONT'D

SCHEDULE "C"

## BARNWELL CEMETERY MONUMENT/MEMORIAL TABLET

All foundations, headstones, or other items associated with a grave shall be confined within the boundaries of the respective plots and all headstones and monuments shall be placed in such a manner as to maintain wherever possible a proper alignment placed in line at the head of the grave.

## REINFORCED CONCRETE BASE

A rectangular piece of support concrete of four (4") inch thickness so places as to be level with the surrounding ground, and four (4") inches wider all around than the base of the monument foot, stone, or tablet to be placed upon it. Not to exceed a total width of forty-eight (48") inches and a depth of thirty-six (36") inches for single graves and a width of ninety-four (94") inches and depth of thirty-six inches for double graves. Covers for entire graves shall not be permitted in the Barnwell Cemetery.

#### VASES

Vase supports built into the base of the monument and must allow four (4) inches of clearance on all sides from the edges of the base.

## **MONUMENT**

A Memorial of stone or other material which projects above the surrounding ground shall have a maximum width of forty (40") inches for single graves and eighty-six (86) inches for double graves. A maximum depth of twenty-eight (28") inches, and maximum height of thirty-six (36") inches.

# **MEMORIAL TABLET**

Authorized: \_\_\_\_\_

A Memorial of stone or other material which is placed, is to be level with the surrounding ground. Maximum width of forty-eight (48") for single graves, and ninety-four (94") inches for double graves with a maximum depth of twenty-four (24") inches.

Only Licensed Firms Relating or Handling Monuments may Install Concrete Bases

APPLICATION FOR PERMIT 1 AS DESCRIBED BELOW:				OR TABLET ON THE GR	AVE
NAME		DATE OF DEATH			
GRAVE DESCRIPTIO	N				
	Row	Block	Lot		
Contractor		Address		Telephon	e
Single Permit Fee:	\$50.00	X (No. of Pe		Total \$	